

**ELEVATION / BUILDING
SECTION GENERAL NOTES**

- ON SYMMETRICAL DRAWINGS, ALL NOTES AND DIMENSIONS SHOWN ON ONE-HALF OF DRAWING SHALL APPLY TO BOTH HALVES OF DRAWINGS.
- PROVIDE HIGH PERFORMANCE COATINGS AT ALL EXTERIOR FERROUS METALS (STRUCTURAL AND DECORATIVE).
- INTERIOR VIEWS IN BUILDING SECTIONS ARE TYPICALLY SIMPLIFIED FOR CLARITY. REFER TO LARGER SCALED INTERIOR ELEVATIONS FOR ADDITIONAL INFORMATION.
- FOOTINGS AND FOUNDATIONS ARE SHOWN FOR ILLUSTRATION ONLY. REFER TO STRUCTURAL DRAWINGS FOR EXTENT OF WORK.
- ALL DOWNSPOUTS ARE TO BE 6" TYPICAL, U.N.O.
- REFERENCE MEP & CIVIL DRAWINGS FOR FULL SCOPE OF M.E.P. & CIVIL WORK.
- PROVIDE CAST IRON BOOTS AT ALL DOWNSPOUTS AT GRADE, U.N.O.
- SEE **SHEET G100** FOR INFORMATION ON RATED EXTERIOR WALLS.
- SEE **SHEET A400** FOR EXTERIOR ENVELOPE TYPES AND **SHEET A002** FOR EXTERIOR WALL ASSEMBLY TYPES.
- MATCH MASONRY COURSING TO GRAPHIC COURSING IN ELEVATIONS. ALERT THE ARCHITECT OF MIS-ALIGNMENTS IN THE FIELD.

**STOREFRONT & CURTAINWALL
GENERAL NOTES**

- VERIFY ALL DIMENSIONS IN FIELD PRIOR TO FABRICATION.
- SEE SPECIFICATIONS FOR GLASS TYPES.
- DIMS SHOWN ARE NOMINAL AND/OR ROUGH OPENINGS. CONTRACTOR TO ACCOUNT FOR JOINTS, SHIMS, SEALANT, ETC.
- CONTRACTOR RESPONSIBLE TO COORDINATE ALL ALUMINUM FRAMES WITH ALL RELEVANT DETAILS DEPICTED THROUGHOUT DRAWINGS.
- COORDINATE ALL ALUMINUM FRAMES WITH SPECIFICATION REQUIREMENTS, INCLUDING BUT NOT LIMITED TO PROVIDING ENGINEERING TO VERIFY WIND LOADING CRITERIA IS MET IN ALL CASES. SEE STRUCTURAL DRAWINGS.
- ALUMINUM FRAME DRAWINGS REPRESENT DESIGN INTENT. SHOP DRAWINGS ARE REQUIRED PRIOR TO FABRICATION.
- NO FRAMES SHALL BE DELIVERED OR INSTALLED PRIOR TO APPROVED SUBMITTALS WHICH INCLUDE ENGINEERING DATA AND SHOP DRAWINGS BASED ON MEASUREMENTS VERIFIED IN FIELD.
- COORDINATE ALL HARDWARE WITH DOOR SCHEDULE AND SPECIFICATIONS.
- SEE DOOR SCHEDULE FOR TYPICAL DOOR TYPES, WHICH INCLUDE ALUMINUM DOORS INSTALLED IN ALUMINUM FRAMES.
- SEE DOOR SCHEDULE FOR TYPES AND DETAILS OF DOORS IN ALUMINUM STOREFRONT FRAMES.
- JOINTS SHOWN IN ELEVATION BETWEEN STOREFRONT MEMBERS ARE NOT INTENDED TO SHOW ACTUAL JOINT LOCATIONS.
- FRAME TYPES, AS DEPICTED, REFLECT THE EXTERIOR CONDITION OF THE FRAME.
- DIMENSIONS ARE PROVIDED FOR DESIGN INTENT ONLY. INSTALLER SHALL FIELD VERIFY ALL OPENINGS PRIOR TO FABRICATION OF STOREFRONT ASSEMBLIES AND SHALL ALLOW FOR SHIM SPACES, JOINTS, SEALANT, ETC. AS REQUIRED.
- MAINTAIN 1" CLEAR AIR SPACE AT INSIDE FACE OF ALL SPANDREL PANELS & BATT INSULATION.
- PROVIDE MANUALLY-OPERATED ROLLER SHADES AT LOCATIONS INDICATED.
- U.N.O. FILL SHIM SPACE AT SPICW & R.O. WITH L.D.F.
- U.N.O. ALL STOREFRONT SYSTEMS ARE 2" X 4" 12"

- SHADES COVER FULL HEIGHT OF GLAZING, U.N.O.
- ALIGN JOINTS IN SHADE FABRIC WITH MAJOR VERTICAL MULLIONS, TYP.
- ROLLER-SHADES SHALL COVER OPERABLE SASH WITHOUT INTERRUPTION.

GLAZING TYPES

GL-01	CLEAR FLOAT GLASS
GL-01T	CLEAR FLOAT GLASS, FULLY TEMPERED
GL-05	CLEAR LOW-E COATED INSULATED GLASS
GL-05T	CLEAR LOW-E COATED INSULATED GLASS, FULLY TEMPERED

WINDOW FRAME TYPES

TAG	DESCRIPTION
ES-#	EXTERIOR STOREFRONT
IS-#	INTERIOR STOREFRONT

KEYNOTES

KEYNOTE	DESCRIPTION
04 2613A	MASONRY VENEER, FACE BRICK, UTILITY
07 7200B	ROOF ACCESSORIES - SHEET METAL FASCIA TRIM
08 4113A	ALUMINUM-FRAMED ENTRANCES AND STOREFRONTS - EXTERIOR
08 6200A	UNIT SKYLIGHTS
09 9213A	EXTERIOR MINERAL STAINS
26 5600A	EXTERIOR LIGHTING

